



FEATURES

- Powering a 4 ~ 20mA DC current loop.
- Output voltage: DC 24V.
- Two isolated output.
- 4 way isolated.
- DIN rail type.



ORDERING INFORMATION

MODEL: S4T-DWD-A4-

DC Input Range (Input Resistance)

A4: 4 ~ 20mA ($\leq 50\Omega$)

DC Output Range - 1 (Output Resistance)

V2: 0 ~ 5V ($\geq 1K\Omega$)

V3: 1 ~ 5V ($\geq 1K\Omega$)

V4: 0 ~ 10V ($\geq 1K\Omega$)

A1: 0 ~ 1mA (0 ~ 10K Ω)

A2: 0 ~ 10mA (0 ~ 1K Ω)

A3: 0 ~ 20mA (0 ~ 500 Ω)

A4: 4 ~ 20mA (0 ~ 500 Ω)

00: Option

DC Output Range - 2 (Output Resistance)

V2: 0 ~ 5V ($\geq 1K\Omega$)

V3: 1 ~ 5V ($\geq 1K\Omega$)

V4: 0 ~ 10V ($\geq 1K\Omega$)

A1: 0 ~ 1mA (0 ~ 10K Ω)

A2: 0 ~ 10mA (0 ~ 700 Ω)

A3: 0 ~ 20mA (0 ~ 350 Ω)

A4: 4 ~ 20mA (0 ~ 350 Ω)

00: Option

Power Supply


A: AC / DC 90~ 260V B: DC 20 ~ 60V

0: Option


SPECIFICATION

Accuracy	$\pm 0.1\%$ RO.
Response time	≤ 400 msec. 0 ~ 99%
Output ripple	$\leq 0.5\%$ RO. (Peak)
Power supply	AC / DC 90~260V, 50/60Hz DC 20 ~ 60V
Power consumption	at 240V, \leq AC 7.5VA, \leq DC 6W 110V, \leq AC 4VA, \leq DC 4W
Supply output	DC 24V $\pm 10\%$, Max. 30mA
Temperature coefficient	$\leq 0.015\%$ / $^{\circ}$ C
Operating temperature	- 5 ~ 50 $^{\circ}$ C
Storage temperature	-10 ~ 70 $^{\circ}$ C
Max. relative humidity	90%
Isolation	Input/Output/Power
Dielectric strength	AC 1.8KV/min.
	Output 1/ Output 2 AC 1.0KV/min.
Insulation resistance	$\geq 100M\Omega$, DC 500V
Electrostatic discharge	IEC 61000-4-2.
Electromagnetic fields immunity	IEC 61000-4-3.
Electrical transient in burst	IEC 61000-4-4.
Withstanding impulse voltage	IEC 61000-4-5.
Immunity to voltage dips	IEC 61000-4-11.
Weight	Abt.140g

THE OUTSIDE DIMENSION (UNIT: mm)



DEMAND FOR MOUNTING (UNIT: mm)



SCHEMATIC CIRCUITRY & CONNECTION DIAGRAM

