

RTD TRANSMITTER (ISOLATED)

S4T-RR



FEATURES


- Converting a RTD input into a standard process signal.
- Automatically eliminated for wire Resistance
(3 wires connection).
- Isolation: Input to output to power.
- DIN rail type.



ORDERING INFORMATION

MODEL:S4T-RR- □□□□	
Input RTD	
P: Pt 100	0:Option
C: Cu 50	
Input Temperature Range	
A: -100 ~ 100°C	E: 0 ~ 50°C
B: -50 ~ 50°C	F: 0 ~ 100°C
C: -50 ~ 100°C	G: 0 ~ 200°C
D: -50 ~ 200°C	H: 0 ~ 400°C
0: Option	
DC Output Range (Output Resistance)	
V2: 0 ~ 5V	(\geq 1K Ω)
V3: 1 ~ 5V	(\geq 1K Ω)
V4: 0 ~ 10V	(\geq 1K Ω)
A1: 0 ~ 1mA	(0 ~ 10K Ω)
A2: 0 ~ 10mA	(0 ~ 1.5K Ω)
A3: 0 ~ 20mA	(0 ~ 750 Ω)
A4: 4 ~ 20mA	(0 ~ 750 Ω)
00: Option	
Power Supply	
A: AC / DC 90 ~ 260V	B: DC 20 ~ 60V
0: Option	


THE OUTSIDE DIMENSION (UNIT: mm)



SPECIFICATION

Accuracy	$\pm 0.1\%$ RO.
Response time	$\leq 400\text{msec}$. 0 ~ 99%
Output ripple	$\leq 0.5\%$ RO. (Peak)
Power supply	AC / DC 90V ~ 260V, 50/60Hz DC 20V ~ 60V
Power consumption	at 240V, \leq AC 6.5VA, \leq DC 5W 110V, \leq AC 4.5VA, \leq DC 4W
Temperature coefficient	$\leq 0.015\%/\text{°C}$
Operating temperature	- 5 ~ 50°C
Storage temperature	- 10 ~ 30°C
Max. relative humidity	0 ~ 90%
Isolation	Input/Output/Power
Dielectric strength	AC 1.8KV/min.
Insulation resistance	$\geq 100\text{M}\Omega$, DC 500V
Electrostatic discharge	IEC 61000-4-2.
Electromagnetic fields immunity	IEC 61000-4-3.
Electrical transient in burst	IEC 61000-4-4.
Withstanding impulse voltage	IEC 61000-4-5.
Immunity to voltage dips	IEC 61000-4-11.
Weight	Abt.140g

DEMAND FOR MOUNTING (UNIT: mm)



SCHEMATIC CIRCUITRY & CONNECTION DIAGRAM

